

Datum: 15.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## 2/2-potni el.mag. ventil NC, direk. upr., 230 V, 50 Hz

Kategorija: [Solenoid valve, NC, 230 V, 50 Hz, high pressures](#)  
Šifra: **116582RIE**

### Kratek opis

2/2-way solenoid valve, Stainless steel, NC, directly operated, 230 V, 50 Hz, Medium temp. max. 80°C/90°C, G 1/2, PN 0-30 bar  
Standard series available in two different versions:  
-Directly operated  
-Pilot-operated  
Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4.  
Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4.  
Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

### Tehnične Specifikacije

|                             |                                   |
|-----------------------------|-----------------------------------|
| IP zaščita                  | IP 65                             |
| Navoj                       | G 1/2                             |
| Notranji deli               | Stainless steel                   |
| Ohišje                      | Stainless steel 1.4301            |
| Sedež ventila               | Stainless steel 1.4301            |
| Standardni navoj            | G thread acc. to DIN EN ISO 228-1 |
| Tesnilo                     | FPM                               |
| Vrsta                       | 1                                 |
| DN                          | 3                                 |
| Max. obratovalni tlak [bar] | 30                                |
| B [mm]                      | 52.0                              |
| A [mm]                      | 85.0                              |
| C [mm]                      | 87.0                              |