

Datum: 13.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

3-pot. krog. ventil, Stinard, L-izpust, nikljana med., 1

Kategorija: [3-way ball valves standard type with L-bore](#)
Šifra: **103379RIE**

Kratek opis

3-way ball valve, Standard, L-hole, nickel-plated brass,
Medium / ambient temp. -10 °C to 120 °C, Rp 1, DN 25, PN
max. 40 bar
3-way ball valves with full bore for diverting media.
Applications: Water, non-toxic gases, plumbing and heating
systems, oils, general industrial applications, diesel fuel

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Material navojev	Brass with a bare metal surface
Navoj	Rp 1
Notranji deli	Nickel-plated brass
Ohišje	Nickel-plated brass
Ročica	Aluminium, painted black
Standardni navoj	Rp thread acc. to ISO 7-1
Tesnilo	PTFE
DN	25
PN [bar]	40
B [mm]	80.0
L [mm]	89.0
A [mm]	120.0
Max. sobna temperatura [°C]	120
Max. temperatura medija [°C]	120