

Datum: 15.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Cilinder kratkega hodadelujoč v dveh smerehbatØ 80hod 30G 1/4

Kategorija: [Metalwork](#)  
Šifra: **105947RIE**

(slika je simbolična)

### Kratek opis

Short stroke cylinder, double-acting, Magnet, Piston Ø 80, Stroke 30, G 1/4, Working pressure max. 10 bar, Temp. -10 °C to 80 °C  
Suitable for installation in limited spaces.  
Supplied with magnet.  
Suitable for filtered compressed air, lubricated (ensure continuity) or unlubricated.

### Tehnične Specifikacije

|                                |                                        |
|--------------------------------|----------------------------------------|
| Min. temperaturno območje [°C] | -10                                    |
| Bat                            | Aluminium/PTFE                         |
| Batnica                        | C45 steel, hard chrome-plated          |
| Batnica IT                     | M10                                    |
| Cushioning                     | non-cushioned                          |
| Ffunkcija                      | double-acting                          |
| Gewinde Kolbenstange           | female piston rod                      |
| Glava                          | Aluminium                              |
| Magnet                         | with magnet                            |
| Ovoj                           | C45 steel, hard chrome-plated          |
| Povezava                       | G 1/4                                  |
| Tesnilo batnice                | NBR (additional charge for PU and FKM) |
| Min. nastavljeni tlak [bar]    | 0.4                                    |
| Max. delovni tlak [bar]        | 10                                     |
| Stroke [mm]                    | 30                                     |
| Bat Ø [mm]                     | 80                                     |
| Max. temperaturno območje [°C] | 80                                     |