

Datum: 16.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Dvojna Hitre spojke DN 7.2, G 1/4 notranji navoj, »R26EMS«

Kategorija: [Distributor, 2 quick disconnect coupl. DN 7.2, IT](#)
Šifra: **117927RIE**

Kratek opis

Distributor with 2 quick-connect couplings I.D. 7.2, »R26EMS«, Bright brass, G 1/4 IT, Operating pressure 0 - 35 bar

2-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2.

Available with threaded connection inside or outside.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Ohišje	Brass with a bare metal surface
Povezava	G 1/4 IT
Sestava distributerja	Brass with a bare metal surface, G 3/8 IT
Spojke	DN 7.2, brass with a bare metal surface, G 3/8 ET
Tesnilo	Industrial adhesives, medium strength
Varovaka	Industrial adhesives, medium strength
Max. obratovalni tlak [bar]	35
Višina [mm]	75.0
Premier [mm]	90.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100