



(slika je simbolična)

## El. priključek (večpolni 25-pol, IP 65), vtičnica IP 67 1 m kabel

Kategorija: [Metalwork](#)  
Šifra: **106700RIE**

### Kratek opis

Electrical connection (multipole 25-pole, IP 65), Socket IP 67, 25-pole, with 1 m cable

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates.

Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Monostable (non-latching) version of manual control also available on request.

The operating pressure is based on the installed input plates.

### Tehnične Specifikacije

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Min. temperaturno območje [°C] | -10                                     |
| IP zaščita                     | IP 65                                   |
| Opis                           | IP 67 connector, 25-pin, with 1 m cable |
| Poskusno                       | Max. 16 (e.g. 16 spring return valves)  |
| Ročno upravljanje              | latching                                |
| Vhodna moč                     | 0.6 W per pilot                         |
| Max. temperaturno območje [°C] | 60                                      |