



(slika je simbolična)

Filter»FUTURA«Kov. pos.5 µm, Vel.1, G 3/8, Avto.

Kategorija: [Filter with metal bowl and sight glass](#)
Šifra: **156557RIE**

Kratek opis

Filter »FUTURA« with metal container and viewing tube, 5 µm, Size 1, G 3/8, 1.5 - 16 bar, Temp. -10 °C to 50 °C, Fully-automatic
Filters with excellent flow rates in modern design.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Merjenje pretoka	At P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Navoj	G 3/8
Odtok kondenzata	Fully-automatic
Ohišje	PA66 GF60
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Velikost	1
Min. vhodni tlak [bar]	1.5
Rang filtra [µm]	5
Max. vhodni tlak [bar]	16
C [mm]	34.0
Max. temperaturno območje [°C]	50
A [mm]	52.0
B [mm]	181.0
Pretok [l/min]	2200