

Datum: 13.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Filter reg. iz nerja. jekla 1.4401 G 3/8 1.7 - 17.5 bar

Kategorija: [Stainless steel filter regulators 1.4401](#)  
Šifra: **133542RIE**

### Kratek opis

Stainless steel filter regulator, 1.4401, with secondary venting (reversible), Size 1, G 3/8, Control range 1.7 - 17.5 bar

Stainless steel filter regulators with self-relieving (not for liquid media) for use in the chemical industry, mining, plant construction and special machinery industries, pneumatics, etc.

Pressure setting by hexagon head screw.

### Tehnične Specifikacije

|                              |                                                                          |
|------------------------------|--------------------------------------------------------------------------|
| Membrane                     | NBR/PTFE                                                                 |
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p \leq 1$ bar |
| Navoj                        | G 3/8                                                                    |
| Odtok kondenzata             | Manual drain valve                                                       |
| Ohišje                       | Stainless steel 1.4401 (AISI 316)                                        |
| Tesnilo                      | NBR                                                                      |
| Velikost                     | 1                                                                        |
| Min. krmilno območje [bar]   | 1.7                                                                      |
| Max. krmilno območje [bar]   | 17.5                                                                     |
| Rang filtra [ $\mu$ m]       | 25                                                                       |
| Max. vhodni tlak [bar]       | 30                                                                       |
| Max. sobna temperatura [°C]  | 60                                                                       |
| A [mm]                       | 64.0                                                                     |
| Max. temperatura medija [°C] | 80                                                                       |
| C [mm]                       | 117.0                                                                    |
| B [mm]                       | 271.0                                                                    |
| Pretok [l/min]               | 3200                                                                     |