



(slika je simbolična)

## **Filter reg. »Stinard« Zašč. kletka 40 µm Vel. 2, G 3/8**

Kategorija: [Filter regulator with PC bowl and bowl guard](#)  
Šifra: **100930RIE**

### **Kratek opis**

Filter regulator »Standard«, PC container, Protective cage, 40 µm, Size 2, G 3/8, Input pressure max. 16 bar, 0.5 - 10 bar  
Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

### **Tehnične Specifikacije**

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 3/8                                                                |
| Odtok kondenzata             | Semi-automatic                                                       |
| Ohišje                       | Die-cast zinc, painted silver                                        |
| Posoda                       | Polycarbonate container with protective cage                         |
| Serijska                     | Standard                                                             |
| Tesnilo                      | NBR                                                                  |
| Min. krmilno območje [bar]   | 0.5                                                                  |
| Velikost                     | 2                                                                    |
| Max. krmilno območje [bar]   | 10                                                                   |
| DN                           | 11                                                                   |
| Max. vhodni tlak [bar]       | 16                                                                   |
| Zaslona manometra max. [bar] | 16                                                                   |
| Rang filtra [µm]             | 40                                                                   |
| Max. sobna temperatura [°C]  | 60                                                                   |
| Max. temperatura medija [°C] | 60                                                                   |
| A [mm]                       | 70.0                                                                 |
| F [mm]                       | 76.5                                                                 |
| C [mm]                       | 120.5                                                                |
| D [mm]                       | 145.9                                                                |
| Pretok [l/min]               | 1500                                                                 |