

Datum: 15.05.2024



(slika je simbolična)

## **Filter regulator »G«, PC zbiralnik, 5 µm, Velikost 400, G 1/2**

Kategorija: [Filter regulator with PC bowl, bowl guard](#)Šifra: **116364RIE**

### **Kratek opis**

Filter regulator »G«, with PC container, Protective cage, Mounting bracket, 5 µm, Size 400, G 1/2, Input pressure max. 10 bar  
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.  
The pressure setting can be locked by pushing the button down.

### **Tehnične Specifikacije**

|                                 |                                                                            |
|---------------------------------|----------------------------------------------------------------------------|
| Merjenje pretoka                | At $P_1 = 8$ bar, $P_2 = 6$ bar<br>and pressure drop $\Delta p = 1$<br>bar |
| Navoj                           | G 1/2                                                                      |
| Odtok kondenzata                | Semi-automatic                                                             |
| Ohišje                          | Die-cast aluminium                                                         |
| Posoda                          | Polycarbonate container<br>with protective cage                            |
| Serija                          | G                                                                          |
| Tesnilo                         | NBR                                                                        |
| Vzmet pokrova motorja           | POM                                                                        |
| Min. krmilno območje<br>[bar]   | 1.5                                                                        |
| Rang filtra [µm]                | 5                                                                          |
| Max. krmilno območje<br>[bar]   | 9                                                                          |
| Max. vhodni tlak [bar]          | 10                                                                         |
| A [mm]                          | 68.0                                                                       |
| Max. sobna temperatura<br>[°C]  | 70                                                                         |
| Max. temperatura medija<br>[°C] | 70                                                                         |
| C [mm]                          | 104.0                                                                      |
| D [mm]                          | 166.5                                                                      |
| B [mm]                          | 270.5                                                                      |
| Velikost                        | 400                                                                        |
| Pretok [l/min]                  | 3750                                                                       |