

Datum: 15.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Filter regulator »multifix«, 5 µm, Velikost 3, G 1/2, 0.2 - 6 bar

Kategorija: [Filter regulator with polycarbonate bowl](#)  
Šifra: **100477RIE**

### Kratek opis

Filter regulator »multifix«, PC container, press. gauge, 5 µm, Size 3, G 1/2, Input pressure max. 16 bar, Control range 0.2-6 bar  
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.  
The pressure setting can be locked by pushing the button down.

### Tehnične Specifikacije

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 1/2                                                                   |
| Odtok kondenzata             | Semi-automatic                                                          |
| Ohišje                       | Die-cast zinc                                                           |
| Posoda                       | Polycarbonate container                                                 |
| Serija                       | multifix                                                                |
| Tesnilo                      | NBR                                                                     |
| Vzmet pokrova motorja        | POM-brass                                                               |
| Min. krmilno območje [bar]   | 0.2                                                                     |
| Velikost                     | 3                                                                       |
| Rang filtra [µm]             | 5                                                                       |
| Max. krmilno območje [bar]   | 6                                                                       |
| Zaslon manometra max. [bar]  | 10                                                                      |
| DN                           | 15                                                                      |
| Max. vhodni tlak [bar]       | 16                                                                      |
| Max. sobna temperatura [°C]  | 60                                                                      |
| Max. temperatura medija [°C] | 60                                                                      |
| A [mm]                       | 68.8                                                                    |
| C [mm]                       | 99.0                                                                    |
| D [mm]                       | 147.3                                                                   |
| B [mm]                       | 246.3                                                                   |
| Pretok [l/min]               | 6700                                                                    |