

Datum: 16.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

Filter regulator »variobloc« s kovinsko posodo, Velikost 2, G 1/2

Kategorija: [Filter regulator, metal bowl, incl. sight glass](#)
Šifra: **125312RIE**

Kratek opis

Filter regulator »variobloc«, Metal container incl. viewing tube and pressure gauge, Size 2, G 1/2, Input pressure max. 20 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.

The pressure setting can be locked by pushing the knob down.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Membrane	NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Manual
Ohišje	Die-cast zinc
Posoda	Metal container with viewing tube
Serijska	variobloc
Tesnilo	NBR
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	0.5
Velikost	2
Max. krmilno območje [bar]	10
Zaslon manometra max. [bar]	10
Max. vhodni tlak [bar]	20
Rang filtra [μ m]	40
A [mm]	70.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
C [mm]	98.0
B [mm]	273.0
Pretok [l/min]	5500