

Datum: 15.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Filter z aktivnim ogljem »variobloc« Kov. pos.Vel.2,G 1/2

Kategorija: [Activated carbon filter with metal bowl](#)
Šifra: **125332RIE**

Kratek opis

Active charcoal filter »variobloc« with metal container incl. viewing tube, 0.003 mg/m³, Size 2, G 1/2, Input pressure max. 20 bar
Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

Tehnične Specifikacije

Kakovost zraka po ISO	Class 1 dirt, class 1 oil
8573.1	At P ₁ = 7 bar and pressure drop Δp = 0,2 bar
Merjenje pretoka	G 1/2
Navoj	Metal container with viewing tube
Posoda	variobloc
Serija	
Vsebnost olja v ostanku [mg/m ³]	0.003
Velikost	2
Max. vhodni tlak [bar]	20
C [mm]	26.0
Max. temperatura medija [°C]	50
A [mm]	70.0
Max. sobna temperatura [°C]	80
B [mm]	193.0
Pretok [l/min]	1200