

Datum: 15.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Filter z aktivnim ogljem »variobloc« Zašč. kletkaVel.2,G 1/2

Kategorija: [Activated carbon filter with PC bowl, bowl guard](#)  
Šifra: **125327RIE**

### Kratek opis

Active charcoal filter »variobloc« with PC container and protective cage, 0.003 mg/m<sup>3</sup>, Size 2, G 1/2, Input pressure max. 16 bar  
Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

### Tehnične Specifikacije

|                                              |                                                                  |
|----------------------------------------------|------------------------------------------------------------------|
| Kakovost zraka po ISO 8573.1                 | Class 1 dirt, class 1 oil                                        |
| Merjenje pretoka                             | At P <sub>1</sub> = 7 bar and pressure drop $\Delta p$ = 0,2 bar |
| Navoj                                        | G 1/2                                                            |
| Posoda                                       | Polycarbonate container with protective cage variobloc           |
| Serija                                       |                                                                  |
| Vsebnost olja v ostanku [mg/m <sup>3</sup> ] | 0.003                                                            |
| Velikost                                     | 2                                                                |
| Max. vhodni tlak [bar]                       | 16                                                               |
| C [mm]                                       | 26.0                                                             |
| Max. sobna temperatura [°C]                  | 50                                                               |
| Max. temperatura medija [°C]                 | 50                                                               |
| A [mm]                                       | 70.0                                                             |
| B [mm]                                       | 193.0                                                            |
| Pretok [l/min]                               | 1200                                                             |