



## Filter za visoke pritiske do 40 bar, 40 µm, G 1/2

Kategorija: [Filters for high pressures up to 40 bar](#)

Šifra: **101161RIE**

(slika je simbolična)

### Kratek opis

Filter for high pressures up to 40 bar, with manual bleeder valve, 40 µm, G 1/2, Medium temperature max. 60 °C  
Centrifugal separators with a sintered filter element.

### Tehnične Specifikacije

|                                 |                                                             |
|---------------------------------|-------------------------------------------------------------|
| Merjenje pretoka                | At $P_2 = 6$ bar and<br>pressure drop $\Delta_p = 1$<br>bar |
| Navoj                           | G 1/2                                                       |
| Odtok kondenzata                | Manual drain valve                                          |
| Ohišje                          | Aluminium                                                   |
| Posoda                          | Brass                                                       |
| C [mm]                          | 32.5                                                        |
| Max. vhodni tlak [bar]          | 40                                                          |
| Rang filtra [µm]                | 40                                                          |
| Max. temperatura medija<br>[°C] | 60                                                          |
| A [mm]                          | 65.0                                                        |
| Max. sobna temperatura [°C]     | 90                                                          |
| B [mm]                          | 194.0                                                       |
| Pretok [l/min]                  | 2650                                                        |