

Datum: 16.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Glicerinski manometer, CrNi jeklo, G 1/2, 0 - 40 bar, Ø 100

Kategorija: [Wika](#)
Šifra: **134038RIE**

(slika je simbolična)

Kratek opis

Glycerine pressure gauge CrNi steel design, Connection, rear, eccentric, G 1/2, Goods class 1.0, Measure. range 0 - 40 bar, Ø 100

Glycerine-filled bourdon-tube pressure gauge, CrNi steel type.

For use in the chemical/petrochemical process industry, power stations, machinery and industrial plant engineering.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material	CrNi steel
Material Prozessanschluss	CrNi steel
Položaj povezave	rear, excentrical
Povezava	G 1/2
Prednje steklo	Laminated safety glass
Spodnja/Zgornja meja območja	Positive pressure
Razred točnosti	1.0
Stopnja rasti na območju skale - bar [bar]	1
Merilno območje max. bar	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	100
Premjer [mm]	100
Vrsta	233.50