



(slika je simbolična)

Glicerinski manometer, CrNi jeklo, G 1/4, 0 - 10 bar, Ø 63

Kategorija: [Wika](#)
Šifra: **102320RIE**

Kratek opis

Glycerine pressure gauge CrNi steel design, Connection radial bottom, G 1/4, Goods class 1.6, Measurement range 0 - 10 bar, Ø 63

Glycerine-filled bourdon-tube pressure gauge, CrNi steel type.

For use in the chemical/petrochemical process industry, power stations, machinery and industrial plant engineering. For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material	CrNi steel
Material Prozessanschluss	CrNi steel
Položaj povezave	radial on bottom
Povezava	G 1/4
Prednje steklo	Polycarbonate
Spodnja/Zgornja meja območja	Positive pressure
Stopnja rasti na območju skale - bar [bar]	0.5
Razred točnosti	1.6
Merilno območje max. bar	10
Max. sobna temperatura [°C]	60
Premier [mm]	63
Max. temperatura medija [°C]	100
Vrsta	233.50