



(slika je simbolična)

## Glicerinski manometer, CrNi jeklo, G 1/4, 0 - 250 bar, Ø 63

Kategorija: [Wika](#)  
Šifra: **102386RIE**

### Kratek opis

Glycerine pressure gauge, CrNi steel safety design, Connection radial bottom, G 1/4, Measurement range 0 - 250 bar, Ø 63  
Glycerine-filled bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing). Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere.

### Tehnične Specifikacije

|                                            |                   |
|--------------------------------------------|-------------------|
| Min. sobna temperatura [°C]                | -20               |
| Min. temperatura medija [°C]               | -20               |
| Material                                   | CrNi steel        |
| Material Prozessanschluss                  | CrNi steel        |
| Položaj povezave                           | radial on bottom  |
| Povezava                                   | G 1/4             |
| Prednje steklo                             | Polycarbonate     |
| Spodnja/Zgornja meja območja               | Positive pressure |
| Razred točnosti                            | 1.6               |
| Stopnja rasti na območju skale - bar [bar] | 10                |
| Max. sobna temperatura [°C]                | 60                |
| Premjer [mm]                               | 63                |
| Max. temperatura medija [°C]               | 100               |
| Vrsta                                      | 233.30            |
| Merilno območje max. bar                   | 250               |