

Datum: 14.05.2024



Hidravlična spojka Serija B, poniklj. Med.G 1/2 N.N.

Kategorija: [Hydraulic couplings, female](#)
Šifra: **107730RIE**

(slika je simbolična)

Kratek opis

Hydraulic coupling, Series B, nickel-plated brass, G 1/2 IT, I.D. 12.5, Operating pressure max. 300 bar
Acc. to ISO 7241-1, B Series.

This coupling series combines an extremely small pressure drop with maximum hydraulic power transmission.

Interchangeable with all couplings and plugs manufactured according to the above standard.

The patented pressure eliminator permits disconnection even if back pressure has built up (up to 200 bar).

The pressure eliminator can be used in all applications where there is a risk of pressure build-up after the line has been separated. It allows effortless connection under pressure.

The mating part must be pressureless in order for the eliminator to function optimally.

Areas of application: chemical industry, food technology, automotive, offshore.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-30
Krogla	Stainless steel
Ohišje	Nickel-plated brass
Potisni čep	Steel
Povezava	G 1/2 IT
Sprostitutveni rokav	Steel
Tesnilo	NBR
Ventil	Brass
Vzmet	Stainless steel
DN	12.5
a/f [mm]	33
Volumski pretok (olja) [l/min]	40
Dolžina [mm]	66.0
Max. delovna temperatura [°C]	100
Max. obratovalni tlak [bar]	300