

Datum: 15.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Hitre spojke I.D. 10 Visok przun. navojok G 3/4 N.N.

Kategorija: [Quick disconnect coupling DN 10, female](#)  
Šifra: **107446RIE**

### Kratek opis

Quick-connect coupling I.D. 10, High flow rate, Steel / nickel-plated brass, G 3/4 IT, Pressure 0 - 35 bar, Temp. -20 °C to 100 °C

"

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. 3.5 times as high as the popular DN 7.2 standard coupling) with minimal coupling forces.

Suitable for all applications with an above-average air requirement!

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, Machine and plant engineering, Measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, food technology, aerospace.

"

### Tehnične Specifikacije

|                              |                                   |
|------------------------------|-----------------------------------|
| Min. sobna temperatura [°C]  | -20                               |
| Min. temperatura medija [°C] | -20                               |
| Krogla                       | Stainless steel                   |
| Merjenje pretoka             | at 6 bar and $\Delta p = 0.5$ bar |
| Navojni kos                  | Nickel-plated brass               |
| Povezava                     | G 3/4 IT                          |
| Pritrdilni obroč             | Stainless steel                   |
| Sedež ventila                | Brass                             |
| Sprostitutveni rokav         | Nickel-plated brass               |
| Telo ventila                 | Steel, QPQ treated                |
| Tesnilo                      | NBR                               |
| Ventil                       | Brass                             |
| Vzmet                        | Stainless steel                   |
| DN                           | 10                                |
| a/f [mm]                     | 32                                |
| Max. obratovalni tlak [bar]  | 35                                |
| Dolžina [mm]                 | 73.7                              |
| Max. sobna temperatura [°C]  | 100                               |
| Max. temperatura medija [°C] | 100                               |
| Pretok                       | 3600 l/min (air)                  |