

Datum: 15.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Hitre spojke I.D. 2.7, Inox 1.4404, cev 4x3

Kategorija: [Quick disc. coupling DN2.7, 1.4404, hose connector](#)
Šifra: **107113RIE**

Kratek opis

Quick-connect coupling I.D. 2.7, Stainless steel 1.4404, Hose connection 4x3, Operating pressure 0 - 35 bar, Temp. -15°C to 200°C

"

One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel 1.4404
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Stainless steel 1.4404
Povezava	Hose connection 4x3
Pritrdilni obroč	Stainless steel 1.4404
Rokav	Stainless steel 1.4404
Telo ventila	Stainless steel 1.4404
Tesnilo	FKM
Vzmet	Stainless steel 1.4404
DN	2.7
a/f [mm]	9
Dolžina [mm]	34.0
Pretok	165 l/min (air)
Max. sobna temperatura [°C]	200
Max. temperatura medija [°C]	200