

Datum: 16.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Hitre spojke z Z.N. I.D. 2.7iz med.M5 Z.N.

Kategorija: [Quick disconnect coupling DN 2.7, male](#)  
Šifra: **107069RIE**

### Kratek opis

Quick-connect coupling I.D. 2.7, bright brass, M5 ET,  
Operating pressure 0 - 35 bar, Medium / ambient temp. -20  
°C to 100 °C

"

One-hand quick disconnect couplings, one side sealing,  
extremely compact with a large bore and only a small  
pressure drop.

To prevent injuries or a "whiplash" effect, we recommend  
that the plug-in nipple is held with one hand during  
uncoupling.

Areas of application: Pneumatic system, machine and plant  
engineering, measurement, monitoring and control systems,  
manufacturing industry, medical technology, chemical /  
pharmaceutical industry, automotive.

"

### Tehnične Specifikacije

|                              |                                                              |
|------------------------------|--------------------------------------------------------------|
| Min. sobna temperatura [°C]  | -20                                                          |
| Min. temperatura medija [°C] | -20                                                          |
| Delovni tlak                 | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Krogla                       | Stainless steel                                              |
| Merjenje pretoka             | at 6 bar and $\Delta p = 0.5$ bar                            |
| Ohišje                       | Brass with a bare metal surface                              |
| Povezava                     | M5 ET                                                        |
| Pritrdilni obroč             | Stainless steel                                              |
| Rokav                        | Brass with a bare metal surface                              |
| Telo ventila                 | Brass with a bare metal surface                              |
| Tesnilo                      | NBR                                                          |
| Vzmet                        | Stainless steel                                              |
| DN                           | 2.7                                                          |
| a/f [mm]                     | 9                                                            |
| Dolžina [mm]                 | 26.0                                                         |
| Max. sobna temperatura [°C]  | 100                                                          |
| Max. temperatura medija [°C] | 100                                                          |
| Pretok                       | 165 l/min (air)                                              |