

Datum: 16.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Komp. cilind. del. v dveh smereh, bat Ø 100hod 60G 1/4

Kategorija: [Compact cylinder, double-acting, with magnet](#)  
Šifra: **115252RIE**

### Kratek opis

Compact cylinder »ACP«, double-acting, Piston Ø 100,  
Stroke 60, Connection G 1/4, Working pressure 1-10 bar,  
Temp. -20 °C to 70 °C  
Characterised by a very short and compact design.  
Suitable for filtered, unlubricated or lubricated compressed  
air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                   |
|--------------------------------|-------------------|
| Min. temperaturno območje [°C] | -20               |
| Bat                            | Aluminium         |
| Batnica                        | Steel             |
| Batnica IT                     | M12x1.75          |
| Ffunkcija                      | double-acting     |
| Gewinde Kolbenstange           | female piston rod |
| Magnet                         | with magnet       |
| Ovoj                           | Aluminium         |
| Povezava                       | G 1/4             |
| Serijska                       | ACP series        |
| Tesnilo                        | NBR               |
| Min. delovni tlak [bar]        | 1                 |
| Max. delovni tlak [bar]        | 10                |
| Batnica Ø [mm]                 | 25                |
| Stroke [mm]                    | 60                |
| Max. temperaturno območje [°C] | 70                |
| Bat Ø [mm]                     | 100               |