

Datum: 15.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Komp. cilind. del. v dveh smereh, bat Ø 40hod 100G 1/8

Kategorija: [Compact cylinder, double-acting, with magnet](#)
Šifra: **115356RIE**

Kratek opis

Compact cylinder »ACP«, double-acting, Piston Ø 40, Stroke 100, Connection G 1/8, Working pressure 1-10 bar, Temp. -20 °C to 70 °C
Characterised by a very short and compact design.
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Steel
Batnica IT	M6x1.0
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod
Magnet	with magnet
Ovoj	Aluminium
Povezava	G 1/8
Serijska	ACP series
Tesnilo	NBR
Min. delovni tlak [bar]	1
Max. delovni tlak [bar]	10
Batnica Ø [mm]	12
Bat Ø [mm]	40
Max. temperaturno območje [°C]	70
Stroke [mm]	100