



(slika je simbolična)

## Kontrolni ventil nagnjen sedež nerjavno jeklo, G 3/4, 0.2 bar

Kategorija: [Unidirectional valves angle-seat, stainless steel](#)  
Šifra: **103835RIE**

### Kratek opis

Check valve inclined seat design stainless steel,  
Medium/ambient temp. -10°C to 230°C, G 3/4, max 40 bar,  
Opening pressure 0.2 bar

### Tehnične Specifikacije

|                               |                      |
|-------------------------------|----------------------|
| Min. delovna temperatura [°C] | -10                  |
| Min. sobna temperatura [°C]   | -10                  |
| Min. temperatura medija [°C]  | -10                  |
| Navoj                         | G 3/4                |
| Notranji deli                 | Stainless steel      |
|                               | 1.4401 / 1.4408      |
| Ohišje                        | Stainless steel      |
|                               | 1.4401 / 1.4408      |
| Standardni navoj              | G thread acc. to DIN |
|                               | EN ISO 228-1         |
| Tesnilo                       | FKM                  |
| Min. tlak odpiranja [bar]     | 0.2                  |
| a/f [mm]                      | 32                   |
| Max. obratovalni tlak [bar]   | 40                   |
| B [mm]                        | 68.0                 |
| L [mm]                        | 76.0                 |
| Max. delovna temperatura [°C] | 230                  |
| Max. sobna temperatura [°C]   | 230                  |
| Max. temperatura medija [°C]  | 230                  |