

Datum: 15.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Kontrolni ventil nagnjen sedež nerjavno jeklo, G 3/8, 0.2 bar

Kategorija: [Unidirectional valves angle-seat, stainless steel](#)
Šifra: **103833RIE**

Kratek opis

Check valve inclined seat design stainless steel,
Medium/ambient temp. -10°C to 230°C, G 3/8, max 40 bar,
Opening pressure 0.2 bar

Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Navoj	G 3/8
Notranji deli	Stainless steel
	1.4401 / 1.4408
Ohišje	Stainless steel
	1.4401 / 1.4408
Standardni navoj	G thread acc. to DIN
	EN ISO 228-1
Tesnilo	FKM
Min. tlak odpiranja [bar]	0.2
a/f [mm]	27
Max. obratovalni tlak [bar]	40
B [mm]	53.5
L [mm]	66.0
Max. delovna temperatura [°C]	230
Max. sobna temperatura [°C]	230
Max. temperatura medija [°C]	230