



(slika je simbolična)

## krogelni ventil medenina, pnevmatski vklop duple-acting, Rp 3

Kategorija: [Brass ball valves, double-acting actuator](#)  
Šifra: **103531RIE**

### Kratek opis

2-way brass ball valve, Pneumat. actuation drive double-acting, Operating temperature max. 70 °C, Rp 3, DN 80, PN max. 16 bar  
2-way cock, full bore.  
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

### Tehnične Specifikacije

|                                   |                                            |
|-----------------------------------|--------------------------------------------|
| Min. delovna temperatura [°C]     | -20                                        |
| Adapter ventila                   | Supplied as standard                       |
| Material krogelnega ventila       | Nickel-plated brass, with ISO flange plate |
| Navoj                             | Rp 3                                       |
| Pogonski material                 | Anodised aluminium                         |
| Premaz za krogelni ventil         | PTFE / FKM                                 |
| Premaz za pogon                   | NBR                                        |
| Različica                         | double-acting                              |
| Priporočeni vodeni tlak [bar]     | 5.5                                        |
| Max. vodeni tlak aktuatorja [bar] | 10                                         |
| PN [bar]                          | 16                                         |
| D [mm]                            | 68.0                                       |
| Max. delovna temperatura [°C]     | 70                                         |
| DN                                | 80                                         |
| Kot vrtenja [°]                   | 90                                         |
| a/f [mm]                          | 98                                         |
| A [mm]                            | 161.0                                      |
| L [mm]                            | 182.0                                      |
| B [mm]                            | 225.0                                      |