



(slika je simbolična)

## krogelni ventil nerjavno jeklo, Pneumat. vklop, Rp 3/4

Kategorija: [Stainless steel ball valve, double-acting actuator](#)  
Šifra: **103598RIE**

### Kratek opis

2-way stainless steel ball valve, Pneumat. actuation drive, double-acting, Operating temp. -20°C to 70°C, Rp 3/4, PN max. 63 bar  
2-way cock, 3-piece, full bore.  
Pneumatic actuators, double- or single acting version and integrated end-position feedback.  
Standardised interfaces:  
Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.  
Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.  
Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

### Tehnične Specifikacije

|                                   |                                            |
|-----------------------------------|--------------------------------------------|
| Min. delovna temperatura [°C]     | -20                                        |
| Adapter ventila                   | Acc. to NAMUR<br>Stainless steel           |
| Material krogelnega ventila       | 1.4401, with ISO<br>flange plate<br>Rp 3/4 |
| Navoj                             | Anodised aluminium                         |
| Pogonski material                 | PTFE                                       |
| Premaz za krogelni ventil         | NBR                                        |
| Premaz za pogon                   | double-acting                              |
| Različica                         | 5.5                                        |
| Priporočeni vodeni tlak [bar]     | 10                                         |
| Max. vodeni tlak aktuatorja [bar] | 20                                         |
| DN                                | 27.0                                       |
| D [mm]                            | 35                                         |
| a/f [mm]                          | 63                                         |
| Max. obratovalni tlak [bar]       | 70                                         |
| Max. delovna temperatura [°C]     | 80.0                                       |
| L [mm]                            | 90                                         |
| Kot vrtenja [°]                   | 116.0                                      |
| A [mm]                            | 139.0                                      |
| B [mm]                            |                                            |