

Datum: 15.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

krogelni ventil nerjavno jeklo, pnevmatski vklop, Rp 1/2

Kategorija: [Stainless steel ball valve, single-acting actuator](#)
Šifra: **154078RIE**

Kratek opis

Stainless steel ball valve, Pneumatic actuation drive, single-acting, Operating temp. -20 °C to 150 °C, Rp 1/2, PN max. 100 bar

Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperaturno območje [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Stainless steel 1.4401/1.4301/1.4310/1.4408, with ISO flange
Navoj	Rp 1/2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	single-acting - spring to close
Max. vodeni tlak [bar]	5.6
DN	15
L [mm]	61.0
Max. temperaturno območje [°C]	80
Kot vrtenja [°]	90
PN [bar]	100
B [mm]	147.0
Max. delovna temperatura [°C]	150
A [mm]	221.0