

Datum: 16.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## krogelni ventil, visoki tlak, G notranji navoj, jeklo, G 1

Kategorija: [High-pressure ball valve, steel, G female thread](#)  
Šifra: **103520RIE**

### Kratek opis

Ball valve, High pressure design, G interior thread, Steel,  
Operating temperature -10 °C to 100 °C, G 1, DN 25, PN  
max. 420 bar  
For liquid and lubricating media.  
Available versions:  
- For solderless tube fittings acc. to DIN 2353, lightweight  
series acc. to ISO 8434-1.  
- For solderless tube fittings acc. to DIN 2353, heavy-duty  
series acc. to ISO 8434-1.  
- With female pipe thread acc. to DIN ISO 228-1 (BSP).

### Tehnične Specifikacije

|                                  |                             |
|----------------------------------|-----------------------------|
| Min. delovna temperatura<br>[°C] | -10                         |
| Bore inball                      | Full bore                   |
| Gred izbirnika                   | Steel                       |
| Kontrolno kroglično tesnilo      | POM                         |
| Krogla                           | Hard-chrome plated<br>steel |
| Navoj                            | G 1                         |
| Ohišje                           | Steel                       |
| Tesnilo gredi izbirnika          | NBR                         |
| DN                               | 25                          |
| Max. delovna temperatura<br>[°C] | 100                         |
| L [mm]                           | 115.0                       |
| B [mm]                           | 128.0                       |
| A [mm]                           | 187.0                       |
| Max. obratovalni tlak [bar]      | 420                         |