

Datum: 16.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Linijski filter za manometer, G 1/2 IT, G 1/2 ET, 200 µm

Kategorija: [Metalwork](#)
Šifra: **143860RIE**

Kratek opis

Pressure gauge in-line filter, G 1/2 IT, G 1/2 ET, 200 µm, stainless steel 1.4571, max. 100 bar, Temp. -25 °C to 200 °C

Pressure gauge in-line filters are installed on pressure gauges in dirt-sensitive hydraulic / pneumatic system circuits in order to filter out solids from gaseous and liquid media (floating body retention). Stoppage of small pressure inlet channels and capillary throttles is prevented by their use. Furthermore particles do not jam in dirt-sensitive media chambers and the resulting appearances of a jam are avoided. Preliminary filters act as throttles and dampers with pressure shocks and pressure surges.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-25
Material	Stainless steel 1.4571
Navoj 1	G 1/2 ET
Navoj 2	G 1/2 IT
Razpon tlaka	Max. 100 bar
a/f [mm]	27
Dolžina [mm]	46.0
Max. temperaturno območje [°C]	200
Rang filtra [µm]	200