



(slika je simbolična)

Medprirobnični zaporni ventil, Pneum. vklop, DN 125

Kategorija: [Butterfly valve, with single-acting actuator](#)
Šifra: **103679RIE**

Kratek opis

Intermediate flange blocking flap, Pneumat. actuation drive, single-acting, Operating temp. -15°C to 120°C, DN 125, PN max. 16 bar
Butterfly valves with pneumatic actuator. Pneumatic actuators, double- or single acting version.
For water/steam, seawater, salt water, ester, ketones, alkalis, caustic soda, sodium hydroxide.
Not recommended for hydrocarbons, oils or greases.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Adapter ventila	Supplied as standard, operated by a 3/2- or 5/2-way valve
Disc	Stainless steel CF8M/1.4404
Gred izbirnika	SS416
Ohišje	Grey cast iron GG25 epoxy resin coated, RAL 5015 color
Pogonski material	Anodised aluminium
Premaz za pogon	NBR
Različica	single-acting - spring to close
Tesnilo	EPDM
Tesnilo gredi izbirnika	EPDM
Min. vodeni tlak [bar]	5
Max. vodeni tlak [bar]	5.5
Max. obratovalni tlak [bar]	16
B [mm]	59.0
Kot vrtenja [°]	90
Max. delovna temperatura [°C]	120
H1 [mm]	123.0
DN	125
L [mm]	190.0
H2 [mm]	191.0
H3 [mm]	361.0