



(slika je simbolična)

## Medprirobnični zaporni ventil, Pneum. vklop, DN 50

Kategorija: [Butterfly valve, with single-acting actuator](#)  
Šifra: **103675RIE**

### Kratek opis

Intermediate flange blocking flap, Pneumat. actuation drive, single-acting, Operating temp. -15°C to 120°C, DN 50, PN max. 16 bar  
Butterfly valves with pneumatic actuator. Pneumatic actuators, double- or single acting version.  
For water/steam, seawater, salt water, ester, ketones, alkalis, caustic soda, sodium hydroxide.  
Not recommended for hydrocarbons, oils or greases.

### Tehnične Specifikacije

|                               |                                                           |
|-------------------------------|-----------------------------------------------------------|
| Min. delovna temperatura [°C] | -15                                                       |
| Adapter ventila               | Supplied as standard, operated by a 3/2- or 5/2-way valve |
| Disc                          | Stainless steel CF8M/1.4404                               |
| Gred izbirnika                | SS416                                                     |
| Ohišje                        | Grey cast iron GG25 epoxy resin coated, RAL 5015 color    |
| Pogonski material             | Anodised aluminium                                        |
| Premaz za pogon               | NBR                                                       |
| Različica                     | single-acting - spring to close                           |
| Tesnilo                       | EPDM                                                      |
| Tesnilo gredi izbirnika       | EPDM                                                      |
| Min. vodeni tlak [bar]        | 5                                                         |
| Max. vodeni tlak [bar]        | 5.5                                                       |
| Max. obratovalni tlak [bar]   | 16                                                        |
| B [mm]                        | 47.0                                                      |
| DN                            | 50                                                        |
| H1 [mm]                       | 71.0                                                      |
| Kot vrtenja [°]               | 90                                                        |
| L [mm]                        | 100.0                                                     |
| Max. delovna temperatura [°C] | 120                                                       |
| H2 [mm]                       | 143.0                                                     |
| H3 [mm]                       | 273.0                                                     |