

Datum: 14.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## MikroFilter »multifix-mali«, Kovinska posoda, 0.01 µm, G 1/8

Kategorija: [Microfilter with metal bowl](#)  
Šifra: **100374RIE**

### Kratek opis

Microfilter »multifix-mini« with metal container, 0.01 µm, Size 0, G 1/8, Input pressure max. 16 bar, Med./ambient temp. max. 60°C  
For filtering out solid impurities larger than 0.01 µm.

### Tehnične Specifikacije

|                                              |                                                         |
|----------------------------------------------|---------------------------------------------------------|
| Element filtra                               | Borosilicate-POM                                        |
| Merjenje pretoka                             | At $P_1 = 6$ bar and pressure drop $\Delta_p = 0.1$ bar |
| Navoj                                        | G 1/8                                                   |
| Odtok kondenzata                             | Semi-automatic                                          |
| Ohišje                                       | Die-cast zinc                                           |
| Posoda                                       | Metal container                                         |
| Serijska                                     | multifix-mini                                           |
| Tesnilo                                      | NBR                                                     |
| Rang filtra [µm]                             | 0.01                                                    |
| Vsebnost olja v ostanku [mg/m <sup>3</sup> ] | 0.01                                                    |
| DN                                           | 5                                                       |
| C [mm]                                       | 12.3                                                    |
| Max. vhodni tlak [bar]                       | 16                                                      |
| A [mm]                                       | 40.0                                                    |
| Max. sobna temperatura [°C]                  | 60                                                      |
| Max. temperatura medija [°C]                 | 60                                                      |
| D [mm]                                       | 99.3                                                    |
| Učinkovitost [%]                             | 99.999                                                  |
| B [mm]                                       | 111.6                                                   |
| Pretok [l/min]                               | 230                                                     |