



(slika je simbolična)

MikroFilter »multifix«PC zbir.Protec. cageVel.4,G 3/4

Kategorija: [Microfilter with polycarbonate bowl and bowl guard](#)

Šifra: **133145RIE**

Kratek opis

Microfilter »multifix«, PC container and protective cage, 0.01 μm , Size 4, G 3/4, Input pressure max. 16 bar, Temp. max. 60 °C
For filtering out solid impurities larger than 0.01 μm .

Tehnične Specifikacije

Element filtra	Borosilicate-POM
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 0.1$ bar
Navoj	G 3/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serija	multifix
Tesnilo	NBR
Rang filtra [μm]	0.01
Vsebnost olja v ostanku [mg/m^3]	0.01
Velikost	4
Max. vhodni tlak [bar]	16
DN	20
C [mm]	58.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	85.0
Učinkovitost [%]	99.999
D [mm]	190.0
B [mm]	248.0
Pretok [l/min]	1500