



(slika je simbolična)

MikroFilter »variobloc«Kov. pos.0.01 µmVel.1,G 3/8

Kategorija: [Microfilter with metal bowl, incl. sight glass](#)
Šifra: **125321RIE**

Kratek opis

Microfilter »variobloc«, Metal container incl. viewing tube, 0.01 µm, Size 1, G 3/8, Input pressure max. 20 bar, Temp. max. 50 °C
Borosilicate filter for all applications where compliance with strict compressed air purity requirements is vital.
As the second stage downstream of the standard filter, the micro-filter removes 99.999 % of even the finest remaining particles from water, oil and dirt with practically zero residues (filter rating: 0.01 µm).

Tehnične Specifikacije

Kakovost zraka po ISO	Class 1 dirt, class 1 oil
8573.1	At P ₁ = 7 bar and pressure drop Δp = 0,1 bar
Merjenje pretoka	G 3/8
Navoj	Metal container with viewing tube
Posoda	variobloc
Serija	0.01
Rang filtra [µm]	1
Velikost	Max. vhodni tlak [bar]
Max. vhodni tlak [bar]	20
C [mm]	22.0
A [mm]	48.0
Max. temperatura medija [°C]	50
Max. sobna temperatura [°C]	80
Učinkovitost [%]	99.999
B [mm]	155.0
Pretok [l/min]	420