

Datum: 15.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

MikroFilter za visoke pritiske do 60 bar, 0.01 µm, G 1

Kategorija: [Microfilters for high pressures up to 60 bar](#)
Šifra: **101183RIE**

Kratek opis

Microfilter for high pressures up to 60 bar, manual bleeder valve, 0.01 µm, G 1, Brass container, Operating temp. 0 °C to 90 °C

Fine filter for all applications with particularly strict compressed air purity requirements. Micro-filters should always be used in conjunction with a standard filter connected upstream to trap coarse impurities and protect the micro-filter inserts.

Tehnične Specifikacije

Element filtra	Borosilicate
Merjenje pretoka	At $P_2 = 6$ bar and pressure drop $\Delta_p = 0.5$ bar
Navoj	G 1
Ohišje	Aluminium
Posoda	Brass
Tesnilo	NBR
Rang filtra [µm]	0.01
C [mm]	29.0
Max. vhodni tlak [bar]	60
A [mm]	80.0
Max. delovna temperatura [°C]	90
Učinkovitost [%]	99.9999
B [mm]	196.0
Pretok [l/min]	2300