

Datum: 15.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Naoljevalnik »Stinard-mali« z PC zbiralnik, Velikost 0, G 1/4

Kategorija: [Oil-mist lubricator with polycarbonate bowl](#)
Šifra: **100791RIE**

Kratek opis

Mist oiler »Standard-mini« with PC container, Size 0, G 1/4,
Input pressure max. 16 bar, Medium / ambient temperature
max. 60 °C
Proportional lubricators in compact design, oil can be filled
under pressure.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/4
Ohišje	Die-cast zinc, painted silver
Posoda	Polycarbonate container
Razred olja	CL 32 acc. to DIN 51517- ISO VG 32
Serija	Standard-mini
Tesnilo	NBR
Vidna kupola	PA
DN	5
Max. vhodni tlak [bar]	16
A [mm]	40.0
C [mm]	49.5
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
D [mm]	95.0
B [mm]	144.5
Pretok [l/min]	650