

Datum: 15.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Nit-reducir, G 3/4, G 1/4

Kategorija: [Thread-reducers - POM](#)
Šifra: **136519RIE**

Kratek opis

Thread-reducer, G 3/4, G 1/4, working pressure -0.95 to 16 bar

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications.

All our push-in fittings made of POM have the following approvals:

drinking water DVGW, KTW, FDA and NSF.

Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Tehnične Specifikacije

Min. delovna temperatura v zraku [°C]	-20
Min. delovni tlak [bar]	-0.95
Material	Acetal polymer (POM)
Navoj 1	G 3/4
Navoj 2	G 1/4
Min. delovna temperatura v vodi [°C]	1
Max. delovni tlak [bar]	16
L1 [mm]	21.0
L2 [mm]	35.0
Max. delovna temperatura v zraku [°C]	65
Max. delovna temperatura v vodi [°C]	70