

Datum: 15.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Okrogli cilinder TP delujoč v dveh smereh, bat Ø 16, hod 200, M5

Kategorija: [Metalwork](#)
Šifra: **105709RIE**

Kratek opis

Round cylinder TP (ISO 6432) double-acting, Piston Ø 16, Stroke 200, M5, Working pressure max. 10 bar, Temp. -10 °C to 60 °C
Inexpensive standard version with aluminum pipe and magnet piston.
Suitable for filtered (50 µm), unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Batnica	Stainless steel 1.4301
Cushioning	non-cushioned
Dno	Technopolymer
ET batnice	M6
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Glava	Technopolymer
Magnet	with magnet
Oblika	Connection: Aluminium pipe / end caps flanged
Ovoj	Aluminium alloy, anodised
Povezava	M5
Puša	Technopolymer
Serijska	TP series
Standard	acc. to ISO 6432
Tesnilo batnice	PU
Min. nastavljeni tlak [bar]	0.6
Max. delovni tlak [bar]	10
Bat Ø [mm]	16
Max. temperaturno območje [°C]	60
Stroke [mm]	200