



## Plošč. ventil HDM prik. 8 mm 5/2-potni monostab., uporaba 1 pin

Kategorija: [Metalwork](#)  
Šifra: **106692RIE**

(slika je simbolična)

### Kratek opis

Valve disc for valve terminal HDM, Connect. 8 mm, 5/2-way, monostable (only uses one PIN, Source 2 signals)  
These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates.  
Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.  
Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.  
Monostable (non-latching) version of manual control also available on request.  
The operating pressure is based on the installed input plates.

### Tehnične Specifikacije

|                                |                                                           |
|--------------------------------|-----------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                       |
| IP zaščita                     | IP 65                                                     |
| Material                       | aluminium                                                 |
| Poskusno                       | Max. 16 (e.g. 16 spring return valves)                    |
| Ročno upravljanje              | latching                                                  |
| Vhodna moč                     | 0.6 W per pilot                                           |
| Ffunkcija                      | 5/2-way, monostable (only uses one PIN, Source 2 signals) |
| Max. temperaturno območje [°C] | 60                                                        |
| Pretok [NI/min]                | 800                                                       |