

Datum: 15.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

Poseben filter »Stinard« Zašč. kletka 0.01 µm Vel. 4G 1

Kategorija: [Special filter with PC bowl and bowl guard](#)
Šifra: **100999RIE**

Kratek opis

Special filter »Standard« with polycarbonate container and protective cage, 0.01 µm, Size 4, G 1, Input pressure max. 16 bar

For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

Tehnične Specifikacije

Merjenje pretoka	At $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1
Odtok kondenzata	Manuel
Ohišje	Die-cast zinc, painted silver
Posoda	Polycarbonate container with protective cage
Serija	Standard
Rang filtra [µm]	0.01
Velikost	4
Max. vhodni tlak [bar]	16
DN	25
C [mm]	36.0
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
Učinkovitost [%]	99.999
H [mm]	120.0
A [mm]	133.0
D [mm]	206.0
Pretok [l/min]	7000