



(slika je simbolična)

Predfilter»FUTURA«PC zbir.0.3 µmVel.2,G 1/2Avt.

Kategorija: [Pre-filter with polycarbonate bowl and bowl guard](#)
Šifra: **100166RIE**

Kratek opis

Pre-filter »FUTURA« with PC container and protective cage, 0.3 µm, Size 2, G 1/2, 1.5-16 bar, Temp. -10°C to 50°C, Fully-automatic
Pre-filters in modern design for compliance with strict compressed air purity requirements.
Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Impregnated paper At P ₂ = 6 bar and pressure drop Δ _p = 0.02 bar
Merjenje pretoka	G 1/2
Navoj	Fully-automatic
Odtok kondenzata	PA66 GF60
Ohišje	Polycarbonate container with protective cage
Posoda	Material: Die-cast zinc
Priključni navoj	FUTURA
Serijska	Compressed air, neutral gases
Srednje	0.3
Rang filtra [µm]	1.5
Min. vhodni tlak [bar]	2
Velikost	16
Max. vhodni tlak [bar]	47.8
C [mm]	50
Max. temperaturno območje [°C]	63.0
A [mm]	210.8
B [mm]	500
Pretok [l/min]	