



## **Serv. enota 2-delna »FUTURA-mali« Kov. pos.G 1/4, 0.5-8**

Kategorija: [Service unit, 2-piece with metal bowl](#)  
Šifra: **142506RIE**

(slika je simbolična)

### **Kratek opis**

Service unit 2-part »FUTURA-mini«, Metal container, Standard pressure gauge, Size 0, G 1/4, Control range 0.5-8 bar, Fully-auto.  
Two-piece service units with excellent flow rates in modern design.  
Diaphragm pressure regulator with secondary ventilation.

### **Tehnične Specifikacije**

|                                |                                |
|--------------------------------|--------------------------------|
| Min. temperaturno območje [°C] | -10                            |
| Element filtra                 | Cellpor (PE)                   |
| Membrane                       | NBR                            |
|                                | At $P_1 = 10$ bar, $P_2 = 6.3$ |
| Merjenje pretoka               | bar and pressure drop          |
|                                | $\Delta_p = 1$ bar             |
| Navoj                          | G 1/4                          |
| Odtok kondenzata               | Fully-automatic                |
| Ohišje                         | PA66 GF60                      |
| Posoda                         | Metal container                |
| Priključni navoj               | Plastic                        |
| Serijska                       | FUTURA-mini                    |
| Srednje                        | Compressed air, neutral gases  |
| Tesnilo                        | NBR                            |
| Vidna kupola                   | PC                             |
| Min. krmilno območje [bar]     | 0.5                            |
| Min. vhodni tlak [bar]         | 1.5                            |
| Rang filtra [µm]               | 5                              |
| Max. krmilno območje [bar]     | 8                              |
| Zaslon manometra max. [bar]    | 10                             |
| Max. vhodni tlak [bar]         | 12                             |
| Max. temperaturno območje [°C] | 50                             |
| C [mm]                         | 63.0                           |
| A [mm]                         | 86.0                           |
| B [mm]                         | 196.0                          |
| Pretok [l/min]                 | 800                            |