

Datum: 16.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

Serv. enota 2-delna »G«Kov. pos.5 µmVel. 600G 3/4

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)
Šifra: **116383RIE**

Kratek opis

Service unit 2-part »G«, Metal container, Viewing tube, 5 µm, Size 600, G 3/4, Input pressure max. 10 bar, Control range 1.5-9 bar
Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/4
Odtok kondenzata	Fully-automatic
Ohišje	Die-cast aluminium
Posoda	Metal container with viewing tube
Serija	G
Tesnilo	NBR
Vidna kupola	Brass/POM
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	9
Max. vhodni tlak [bar]	10
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70
C [mm]	144.0
A [mm]	190.0
D [mm]	219.0
B [mm]	363.0
Velikost	600
Pretok [l/min]	4200