



(slika je simbolična)

## Serv. enota 2-delna »multifix«Kov. pos.Vel. 5G 1

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)  
Šifra: **100580RIE**

### Kratek opis

Service unit 2-part »multifix«, Metal container, Viewing tube, Size 5, G 1, Input pressure max. 20 bar, Control range 0.5 - 10 bar

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

### Tehnične Specifikacije

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 1                                                                     |
| Odtok kondenzata             | Semi-automatic                                                          |
| Ohišje                       | Aluminium                                                               |
| Posoda                       | Metal container with viewing tube                                       |
| Serija                       | multifix                                                                |
| Tesnilo                      | NBR                                                                     |
| Vidna kupola                 | Zinc-glass-NBR                                                          |
| Vzmet pokrova motorja        | POM-brass                                                               |
| Min. krmilno območje [bar]   | 0.5                                                                     |
| Velikost                     | 5                                                                       |
| Max. krmilno območje [bar]   | 10                                                                      |
| Zaslona manometra max. [bar] | 16                                                                      |
| Max. vhodni tlak [bar]       | 20                                                                      |
| DN                           | 25                                                                      |
| Rang filtra [ $\mu$ m]       | 40                                                                      |
| Max. sobna temperatura [°C]  | 60                                                                      |
| Max. temperatura medija [°C] | 60                                                                      |
| C [mm]                       | 128.0                                                                   |
| A [mm]                       | 200.0                                                                   |
| D [mm]                       | 255.7                                                                   |
| B [mm]                       | 383.7                                                                   |
| Pretok [l/min]               | 13500                                                                   |