



(slika je simbolična)

Serv. enota 2-delna »Stinard«Zašč. kletkaVel. 3G 1/2

Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)
Šifra: **101055RIE**

Kratek opis

Service unit 2-part »Standard«, PC container, protective cage, Size 3, G 1/2, Input pressure max. 16 bar, Control range 0.5-10 bar
Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc / aluminium, painted silver
Posoda	Polycarbonate container with protective cage
Serija	Standard
Tesnilo	NBR
Vidna kupola	PA
Min. krmilno območje [bar]	0.5
Velikost	3
Rang filtra [μ m]	5
Max. krmilno območje [bar]	10
DN	15
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Manometer $\varnothing$ [mm]	63
C [mm]	130.0
A [mm]	175.0
B [mm]	299.4
Pretok [l/min]	2100