



(slika je simbolična)

Serv. enota 3-delna »Stinard«Kov. pos.Vel. 4G 1 1/2

Kategorija: [Service unit, 3-piece with metal bowl](#)
Šifra: **101087RIE**

Kratek opis

Service unit 3-part »Standard«, Metal container, metal drip cap, Size 4, G 1 1/2, Input press. max. 25 bar, Control ra. 0.5-16 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1 1/2
Odtok kondenzata	Manuel
Ohišje	Die-cast zinc / aluminium, painted silver
Posoda	Metal container
Serijska	Standard
Tesnilo	NBR
Vidna kupola	Zinc-glass-NBR
Min. krmilno območje [bar]	0.5
Velikost	4
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	25
Zaslon manometra max. [bar]	25
DN	35
Rang filtra [μ m]	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Manometer Ø [mm]	63
C [mm]	70.0
B [mm]	316.0
A [mm]	395.0
Pretok [l/min]	5000