



(slika je simbolična)

Serv. enota 3-delna »Stinard«Zašč. kletkaVel.1,G 3/8

Kategorija: [Service unit, 3-piece with PC bowl and bowl guard](#)
Šifra: **101073RIE**

Kratek opis

Service unit 3-part »Standard«, PC container, protective cage, Size 1, G 3/8, Input pressure max. 16 bar, Control range 0.5-10 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc / aluminium, painted silver
Posoda	Polycarbonate container with protective cage
Serija	Standard
Tesnilo	NBR
Vidna kupola	PA
Min. krmilno območje [bar]	0.5
Velikost	1
Rang filtra [μ m]	5
DN	6
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
Manometer $\varnothing$ [mm]	50
C [mm]	51.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
B [mm]	182.6
A [mm]	185.0
Pretok [l/min]	600