



(slika je simbolična)

Servisna enota 3-delna »Stinard-mali« z PC zbiralnik, G 1/4

Kategorija: [Service unit, 3-piece with polycarbonate bowl](#)
Šifra: **100802RIE**

Kratek opis

Service unit 3-part »Standard-mini«, PC container and pressure gauge, G 1/4, Input pressure max. 16 bar, Control range 0.5-10 bar
Compact, three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc, painted silver
Posoda	Polycarbonate container
Serijska	Standard-mini
Tesnilo	NBR
Vidna kupola	PA
Min. krmilno območje [bar]	0.5
DN	5
Rang filtra [μ m]	5
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
C [mm]	49.5
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
D [mm]	102.0
A [mm]	130.0
B [mm]	151.5
Pretok [l/min]	300