

Datum: 14.05.2024



## Sesalna šalčka meh, Okr. 2.5 pregib, Material NBR, FG Ø 20 mm

Kategorija: [Bellows suction pad, round, 2.5 folds, NBR](#)  
Šifra: **108519RIE**

(slika je simbolična)

### Kratek opis

Bellows suction cup, Round 2.5 folds, Material NBR, »FG«, suitable connection nipple IT G 1/8, ET M5 / G 1/8, Ø20mm Robust and hard-wearing suction pad with a single sealing lip.

Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to compensate varying workpiece heights or uneven surfaces or to handle easily damaged parts. It acts as the connecting element between the vacuum generator and the workpiece.

Properties:

- Soft, flexible folds
- Soft, tapered sealing lips
- Supports on the bottom
- High suction force
- Optimum damping effect
- Very good adaptation to curved workpiece surfaces or materials with uneven surfaces

Applications:

- Handling workpieces with extremely uneven surfaces (e.g. pipes)
- Handling easily damaged parts

### Tehnične Specifikacije

|                                                  |             |
|--------------------------------------------------|-------------|
| Primerna povezava priključka z notranjim navojem | M5 / G 1/8  |
| Primerna povezava priključka z zunanjim navojem  | G 1/8       |
| Prostornina [cm <sup>3</sup> ]                   | 2.000       |
| Sesalna sila [N]                                 | 3.8         |
| Ø notranje cevi [mm]                             | 4           |
| Izvlačna sila [N]                                | 12.1        |
| Premer [mm]                                      | 20          |
| Višina priključka z notranjim navojem [mm]       | 27.0 / 28.0 |
| Min. izbočen polmer krivine [mm]                 | 30          |
| Višina priključka z zunanjim navojem [mm]        | 34.0        |